


Engine Model: Weichai WD10G220E23
Gross Power: 162kW(220hp)@2000rpm

Operating Weight: 16,400kg Bucket Capacity: 3m³ New Appearance better performance


## **L55-B5** SPECIFICATIONS

ENGINE	
Emission	Tier 2 / Stage II
Model	Weichai WD10G220E23
Rated Power	162 kW (220 hp) @ 2,000 rpm
Max Torque	900 N⋅m
Displacement	9.726 L
Number of Cylinders	6
LOADER ARM PERFORMANCE	
Tipping Load - Full Turn	11000 kg
Bucket Breakout Force	170 kN
Maximum Dump Angle at Full Height	45°
Dump Clearance at Full Height Discharge	3050 mm
Dump Reach at Full Height Discharge	1110 mm
Maximum Hinge Pin Height	4100 mm
Maximum Digging Depth, Bucket Level	30 mm
Bucket Capacity	3 m <sup>3</sup>
Operating Weight	16400kg
TRANSMISSION	
Transmission Type	Planetary, power shift
Torque Converter	Single stage, four elements
Maximum Travel Speed, fwd	38 km/h
Maximum Travel Speed, rev	15 km/h
Number of Speeds, fwd	2
Number of Speeds, rev	1
AXLES	
Differential Front Type	Conventional
Differential Rear Type	Conventional
Axle Oscillation	±12°
STEERING	
Steering Configuration	Articulated

lisc brake
Hydraulic
shaft control
cal
16PR
1
n
n
1
1
2
1
1



16 Mpa





Steering System Pressure